

PRODUCT CODE

Macrofix ST-125

## 1) DESCRIPTION

<b>Adhesive Type</b>	Solvent based non-flammable adhesive
<b>Application Area</b>	Mainly upholstery industry
<b>Specifications</b>	MACROFIX is a high strenght a universal adhesive for polyethylene, plates or pipes made of rubber foam, polyurethane acustic foams, Nfaf, wood, rubber, leather, cork, felt, rigid PVC, soft foams, metal and other synthetic materials. Specially recommended for producing upholstery.

## 2) PHYSICAL AND CHEMICAL PROPERTIES

<b>Form</b>	Liquid
<b>Color</b>	Yellow
<b>Application Temperature</b>	10-40 °C
<b>Viscosity</b>	700 CPS $\pm$ 100 sec @ 25 °C
<b>Open Time</b>	Medium
<b>Specific Gravity</b>	1.18 $\pm$ 0.02 g/ml
<b>Shelf Life</b>	Approximately 1 year
<b>Solid content</b>	40% $\pm$ 2

## 3) TRADE MARK REGISTRATION®

Except as otherwise noted, all trademarks in this document are trademarks of MAVERA KİMYA in TURKEY and elsewhere.  
® denotes a trademark registered in TURKEY PATENT OFFICE.

## 4) WARNING FOR CUSTOMERS

The data contained herein are furnished for information only and are believed to be reliable. We can not assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. We specially recommend that each prospective user test his proposed application before repetitive use, using this data as a guide.

HAZIRLAYAN	ONAYLAYAN	TARİH
FATİH ÖZLÜ KİMYA TEKNİKERİ	HÜSEYİN BAŞAK KİMYA YÜKSEK MÜHENDİSİ	01.01.2022